

Affected Product Mako G-030
PCN Title Discontinuation of Mako G-030 Cameras
PCN No. 2020-05-27_2 **PCN Issue date** 2020-May-27
Contact info@alliedvision.com

Type of change

- | | |
|---|---|
| <input type="checkbox"/> Regulatory / Compliance | <input type="checkbox"/> Firmware Specification |
| <input type="checkbox"/> Mechanical Specification | <input type="checkbox"/> Accessories Specification |
| <input type="checkbox"/> Electrical Specification | <input checked="" type="checkbox"/> DISC (Discontinued) |
| <input type="checkbox"/> Optical Specification | <input type="checkbox"/> |

Affected item(s) / item number(s)

The following cameras and variants are discontinued:

Item ID	Description
5044	Camera Mako G-030B
5045	Camera Mako G-030C

All Modular Concept and customized variants of the above listed models are also affected by this discontinuation.

Reason for change

ams has discontinued the CMV300 mono and color image sensors used in the above camera models on short notice with a last-time-buy on August 18, 2020.

Change description

The above listed item numbers change over to the status "End of Life" (EOL). Please see the schedule below.

End of life schedule

	Start	End	Remarks
Last time buy period	27.05.2020	05.08.2020	A few days are needed to consolidate the orders.
Last time shipment period	06.08.2020	28.02.2021	
Last warranty period	01.03.2021	28.02.2024	
Last time repair	01.03.2024	28.02.2026	

Repair replacements will be possible depending on component availability.

Customer action request

If you have a demand for Mako G-030 cameras, please get in contact with your Allied Vision Sales Representative immediately.

Orders for cameras in EOL status are confirmed and processed, depending on component availability. Apart from this, apply our [terms and conditions](#).

Possible successor

A potential alternative to the Mako G-030 is the Mako G-040. The below table shows major specification differences between these two models:

Model	Sensor	Size	Pixel Size	Resolution	Frame Rate
Mako G-030	CMV300 (ams)	1/3"	7.4 µm	644 x 484	309 fps
Mako G-040	IMX287 (Sony)	1/2.9"	6.9 µm	728 x 544	286 fps

Besides this, Allied Vision has large portfolio of CCD and CMOS sensor-based cameras with GigE Vision interface available. Please check our [product webpages](#) for further details.

For more specific details and more alternative products, please contact your Allied Vision Support or Sales Representative.

The information provided in this PCN notification are subject to change without notice. For the latest version of this document, please visit the Allied Vision [website](#).

Support:

In case of technical questions please contact our [Support Team](#)

General inquiries:

Please contact our [Inside Sales Team](#)